



RIPPERS

BPI AUTO RESET HEAVY DUTY RIPPER/SUB SOILER 350 & 550 SERIES





RIPPERS

BPI AUTO RESET HEAVY DUTY RIPPER/SUB SOILER 350 & 550 SERIES

TECHNICAL SPECIFICATIONS

Two models are available with working depths from 350mm up to 550mm deep, depending on the model purchased. Top quality components are used in the manufacturing of the BPI Auto Reset Ripper/Sub Soiler. The shape of the tines provides good penetration, even in hard and dry soil conditions. All components used are heat-treated to stand up to the extreme tough conditions these Rippers/Sub Soilers work in. The auto-reset tines and auto-reset leaf spring protection maximises strength and durability in the toughest conditions. In the event of hitting an immovable obstruction, individual leaf springs allow each leg to trip and ride over the obstacles, returning to their original position automatically. A standard tine spacing of 300mm is effective in most conditions, but tine position can be adjusted to suit different situations from 300mm to 600mm. The "bolt-on" bracket provides a flexible construction with optimal possibilities to adjust the tine spacing and at the same time have the option to increase the amount of tines, thus enabling the user to rip/sub soil the land completely and not only in lines. A robust roller to break up clods and seals in moisture is also available as an optional extra for all models.

STOCK CODE	SPECIFICATIONS	TOTAL WIDTH	WORKING DEPTH	WORKING WIDTH	DEPTH CONTROL WHEELS	REQUIRED POWER
MARR 5	5 TINE	2 500mm	200-350mm	1 200-1 800mm	195 x 14"	60-70kW
MARR 7	7 TINE	3 000mm	200-350mm	1 800-2 700mm	195 x 14"	85-90kW
MARR 9	9 TINE	3 900mm	200-350mm	2 400-3 600mm	195 x 14"	110-120kW
MARR 11	11 TINE	4 700mm	200-350mm	3 000-4 500mm	195 x 14"	130-140kW
MARR 13	13 TINE	5 600mm	200-350mm	3 600-5 400mm	195 x 14"	160-180kW
MARR 5/550	5 TINE	2 500mm	200-550mm	1 200-1 800mm	195 x 14"	135-150kW
MARR 7/550	7 TINE	3 000mm	200-550mm	1 800-2 700mm	195 x 14"	175-190kW
MARR 9/550	9 TINE	3 900mm	200-550mm	2 400-3 600mm	195 x 14"	225-245kW
MARR 11/550	11 TINE	4 700mm	200-550mm	3 000-4 500mm	195 x 14"	275-300kW
MARR 13/550	13 TINE	5 600mm	200-550mm	3 600-5 400mm	195 x 14"	325-350kW

* Manufacturer reserves the rights to change the above without any notice.